

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : Multimin 90
Other means of identification : Zinc, copper, manganese, and selenium injection

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For veterinary use only - Injectable supplement for use in Cattle. USE ONLY IN CATTLE BY SUBCUTANEOUS INJECTION
Restrictions on use : No additional information available

1.3. Supplier

Supplier

Axiota U.S. Inc.
2809 East Harmony Road, SUITE #190
Fort Collins, Colorado 80528
United States
T +1 970.372.2302

1.4. Emergency telephone number

Emergency number : +1.970.372.2302

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4 H302 Harmful if swallowed
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H302 - Harmful if swallowed

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US) : P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P301+P312 - If swallowed: Call a POISON CENTER, a doctor if you feel unwell.
P330 - Rinse mouth.
P501 - Dispose of contents/container to Collection point.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

2.61% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
2.61% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
edetic acid	CAS-No.: 60-00-4	≥ 30 – ≤ 45	Eye Irrit. 2A, H319
sodium hydroxide	CAS-No.: 1310-73-2	≥ 5 – ≤ 15	Skin Corr. 1A, H314
zinc oxide	CAS-No.: 1314-13-2	≥ 5 – ≤ 9	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
copper carbonate	CAS-No.: 1184-64-1	≥ 1 – ≤ 3	Acute Tox. 3 (Oral), H301 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
sodium selenite	CAS-No.: 10102-18-8	≥ 0.5 – ≤ 2	Acute Tox. 2 (Oral), H300 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
benzyl alcohol	CAS-No.: 100-51-6	≥ 0.5 – ≤ 2	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact : Wash skin thoroughly with mild soap and water. Get medical attention if symptoms occur.

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause slight irritation.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing agent suitable for surrounding fire. Unsuitable extinguishing media : None known.

5.2. Specific hazards arising from the chemical

Fire hazard : Presents no particular fire or explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Nitrogen oxides. Zinc oxide. Selenium and its oxides. Manganese dioxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Do not enter fire area without proper protective equipment, including respiratory protection. Move containers away from the fire area if this can be done without risk. Use water spray or fog for cooling exposed containers.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing. Wear fire/flame resistant/retardant clothing. Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all contact with skin, eyes, or clothing. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Evacuate unnecessary personnel. Ventilate spillage area. Do not breathe vapors. Do not get in eyes, on skin, or on clothing. Avoid contact with skin and eyes. Do not touch or walk on the spilled product.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate area.

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Avoid release to the environment. Prevent liquid from entering sewers, watercourses, underground or low areas. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Stop leaks if it can be done without personal risk. Small quantities of liquid spill: take up in noncombustible absorbent material and shovel into container for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Flush residue with large amounts of water.

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Ensure good ventilation of the work station. Do not breathe spray, mist, vapors. Wear personal protective equipment. Avoid contact with skin, eyes and clothing.

Hygiene measures

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

: Keep away from food, drink and animal feed. Keep container tightly closed. Containers which are opened should be properly resealed and kept upright to prevent leakage.

Incompatible products

: Strong acids. Strong bases.

Incompatible materials

: Direct sunlight. Heat sources.

Storage area

: Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

sodium hydroxide (1310-73-2)

USA - ACGIH - Occupational Exposure Limits

Local name	Sodium hydroxide
ACGIH OEL Ceiling	2 mg/m ³
Remark (ACGIH)	TLV® Basis: URT, eye, & skin irr
Regulatory reference	ACGIH 2024

USA - OSHA - Occupational Exposure Limits

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Local name	Sodium hydroxide
OSHA PEL TWA	2 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

zinc oxide (1314-13-2)

USA - ACGIH - Occupational Exposure Limits

Local name	Zinc oxide
ACGIH OEL TWA	2 mg/m ³ (R - Respirable particulate matter)
ACGIH OEL STEL	10 mg/m ³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Metal fume fever
Regulatory reference	ACGIH 2022

USA - OSHA - Occupational Exposure Limits

Local name	Zinc oxide
OSHA PEL TWA	5 mg/m ³ (Fume) 15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Monitoring methods

Monitoring methods

Refer to all applicable national, international and local regulations or provisions.

8.2. Appropriate engineering controls

Appropriate engineering controls : Handle in accordance with good industrial hygiene and safety procedures. Provide local exhaust or general room ventilation. Avoid all unnecessary exposure.

Environmental exposure controls : Avoid release to the environment. Prevent entry to sewers and public waters.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Personal protective equipment should be chosen according to the NIOSH standards and in discussion with the supplier of the protective equipment.

Hand protection:

Chemical resistant gloves (according to NIOSH standard). Use rubber gloves. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing. Skin protection appropriate to the conditions of use should be provided

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Color	: Blue
Odor	: odorless
Odor threshold	: No data available
pH	: 8
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1.3 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Hazardous polymerization: Will not occur.

10.4. Conditions to avoid

Direct sunlight. Heat.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Multimin 90	
ATE US (oral)	544.071 mg/kg body weight
Unknown acute toxicity (GHS US)	2.61% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 2.61% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

edetic acid (60-00-4)	
LD50 oral rat	4500 mg/kg
LC50 Inhalation - Rat	30 mg/m ³

zinc oxide (1314-13-2)	
LD50 oral rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 5700 mg/l (4 h)

copper carbonate (1184-64-1)	
LD50 oral rat	159 mg/kg
ATE US (oral)	159 mg/kg body weight

sodium selenite (10102-18-8)	
LD50 oral rat	7 mg/kg
ATE US (oral)	7 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

benzyl alcohol (100-51-6)	
LC50 Inhalation - Rat	> 4178 mg/m ³
ATE US (oral)	500 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Not classified (Not irritating to skin in vitro (OECD 439 method)) pH: 8

Serious eye damage/irritation : Not classified (Not irritating to eyes (OECD 437 method)) pH: 8

Respiratory or skin sensitization : Not classified (No sensitizing reaction was observed for guinea pigs (OECD 406 method))

Germ cell mutagenicity : Not classified

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause slight irritation.
Symptoms/effects after eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects. Do not allow product to spread into the environment.

edetetic acid (60-00-4)	
LC50 - Fish [1]	41 mg/l (96 h)
EC50 - Crustacea [1]	625 mg/l (24 h)

zinc oxide (1314-13-2)	
LC50 - Fish [1]	1.793 mg/l (96 h, Danio rerio)
EC50 - Crustacea [1]	1.7 – 9 mg/l (OECD 202)
LC50 - Fish [2]	0.169 – 2.17 mg/l (ASTM)

zinc oxide (1314-13-2)	
NOEC chronic fish	0.199 mg/l (OECD 215, Fish Juvenile Growth Test)
NOEC chronic crustacea	0.019 mg/l (9 d)
NOEC chronic algae	0.024 mg/l

sodium selenite (10102-18-8)	
LC50 - Fish [1]	1.8 mg/l (96 h)
EC50 - Crustacea [1]	1.1 mg/l (48 h)

12.2. Persistence and degradability

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Multimin 90

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

Multimin 90

Bioaccumulative potential	Not established.
---------------------------	------------------

edetic acid (60-00-4)

BCF - Fish [1]	1.1 (28 d)
----------------	------------

Partition coefficient n-octanol/water (Log Pow)	-3.34
---	-------

12.4. Mobility in soil

Multimin 90

Ecology - soil	No additional information available.
----------------	--------------------------------------

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions. Must not be disposed together with household garbage.

Sewage disposal recommendations : Do not dispose of waste into sewer. Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

Ecological waste information : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

UN-No.(DOT) : UN3082
UN-No. (TDG) : UN3082

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IMDG) : 3082
UN-No. (IATA) : 3082

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s. (zinc oxide ; copper carbonate)
Proper Shipping Name (TDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide ; copper carbonate)
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (zinc oxide ; copper carbonate)
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s. (zinc oxide ; copper carbonate)

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 9
Hazard labels (DOT) : 9



TDG

Transport hazard class(es) (TDG) : 9
Hazard labels (TDG) : 9



IMDG

Transport hazard class(es) (IMDG) : 9
Hazard labels (IMDG) : 9



IATA

Transport hazard class(es) (IATA) : 9
Hazard labels (IATA) : 9



Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.4. Packing group

Packing group (DOT) : III
Packing group (TDG) : III
Packing group (IMDG) : III
Packing group (IATA) : III

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN3082

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.

146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.

173 - An appropriate generic entry may be used for this material.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx)

: 155

DOT Packaging Non Bulk (49 CFR 173.xxx)

: 203

DOT Packaging Bulk (49 CFR 173.xxx)

: 241

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Passenger aircraft/rail (49 : No Limit

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : No Limit

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

TDG

UN-No. (TDG)

: UN3082

TDG Special Provisions

: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3).

(2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:

(a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S;

(b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S;

(c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.

(3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment:

(a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or

TDG Special Provisions

(b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS,99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, may be offered for transport, handled or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means of containment and during transport.

(2) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.

Explosive Limit and Limited Quantity Index

: 5 L

Excepted quantities (TDG)

: E1

Emergency Response Guide (ERG) Number

: 171

IMDG

Special provision (IMDG)

: 274, 335, 969

Limited quantities (IMDG)

: 5 L

Excepted quantities (IMDG)

: E1

Packing instructions (IMDG)

: LP01, P001

Packing provisions (IMDG)

: PP1

IBC packing instructions (IMDG)

: IBC03

Tank instructions (IMDG)

: T4

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	: A

IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provision (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

sodium selenite	CAS-No. 10102-18-8	≥ 0.5 – ≤ 2%
-----------------	--------------------	--------------

sodium selenite (10102-18-8)	
CERCLA RQ	100 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb 100lb if the substance is solid in powder form with particle size less than 100 microns, or is in solution or molten form

15.2. International regulations

CANADA

edetic acid (60-00-4)

Listed on the Canadian DSL (Domestic Substances List)

sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

edetiac acid (60-00-4)	
CERCLA RQ	5000 lb

sodium hydroxide (1310-73-2)	
CERCLA RQ	1000 lb

zinc oxide (1314-13-2)
Listed on the Canadian DSL (Domestic Substances List)

copper carbonate (1184-64-1)
Listed on the Canadian DSL (Domestic Substances List)

sodium selenite (10102-18-8)
Listed on the Canadian DSL (Domestic Substances List)

benzyl alcohol (100-51-6)
Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

edetiac acid (60-00-4)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

sodium hydroxide (1310-73-2)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

sodium selenite (10102-18-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

benzyl alcohol (100-51-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

: 10/22/2024

Data sources

: Supplier's safety documents. ECHA (European Chemicals Agency). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 and all its amendments and modifications. C&L Inventory database.

Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.

ACGIH (American Conference of Government Industrial Hygienists). OSHA 29CFR 1910.1200 Hazard Communication Standard. NFPA (National Fire Protection Association). TSCA Chemical Substance Inventory.

Abbreviations and acronyms

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ATE	Acute Toxicity Estimate
zinc oxide (1314-13-2)	
Listed on INSQ (Mexican National Inventory of Chemical Substances)	

Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>. NIOSH Occupational Health Guide for chemical Substances - Vol. II, September, 1978. Fire Protection Guide to Hazardous Materials; 10th edition. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", 5th Edition.

Training advice

: Training staff on good practice.

Full text of hazard classes and H-statements	
H300	Fatal if swallowed
H301	Toxic if swallowed
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Abbreviations and acronyms	
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
EC50	Median effective concentration
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
OEL	Occupational Exposure Limit
SDS	Safety Data Sheet

Multimin 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BCF	Bioconcentration factor
IARC	International Agency for Research on Cancer
OECD	Organisation for Economic Co-operation and Development
NOEC	No-Observed Effect Concentration
VOC	Volatile Organic Compounds
	OSHA (Occupational Safety and Health Administration)
	Globally Harmonized System of Classification and Labelling of Chemicals
	Toxic Substances Control Act
	Time Weighted Average
	Short Term Exposure Limits

NFPA health hazard


: 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard

: 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Indication of changes:

1.3. Supplier.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.